



SPEEDFACE 5 Pro



Face



Live Body
Detection



QR
Code



Mifare



Wi-Fi



TCP/IP



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face Capacity	50,000
Card Capacity	50,000
QR Capacity	50,000
Max User	50,000
Log Capacity	2,00,000



Features

Anti-backlight

DualCoreARM Cortex-A7 Processor

Remotely Firmware Upgradation

Recognition speed 0.5 seconds

5-inch IPS display all-sight LCD touch screen

IP54 Grade Highly finished slim device

Highly reliable and durable

Industrial design, stable performance, and smooth outline

SpeedFace 5 Pro

Communication Interface

Communication	Wi-Fi, TCP/IP, Rs232, USB
---------------	---------------------------

Biometric

Push Data	Yes
Remote firmware update	Yes
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7
OS	Linux
Verification time	<=1 second

Audio/Visual

LCD	5.0" IPS touch screen display
IP Rate	Ip54
Language	English

Access control

Wiegand Out	Yes
Relay	Yes
Push button	Yes
Auxiliary	Input

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	190 x 88 x 17 mm



Auto Focus



Autofill light



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control